



## IZI-PowerCom+


### High Power IZI-link+ PowerLine Communication interface

#### Technical specifications:

<b>Power input:</b>	Operating voltage: Input power: Input current:	48VDC 720W max. 15A max.
<b>Power output:</b>	Output voltage: Output power: Output current:	48VDC IZI-Link+ 720W max. 15A max.
<b>Control I/O:</b>	Data in/output:	IZI-Bus CAN-interface
<b>Connections:</b>	Power input: IZI-Link+ / Power output Data in/output:	1.5 – 2.5mm <sup>2</sup> / 16 – 14AWG [V+] 48VDC, [V-] 0V, [PE] Earth 1.5 – 2.5mm <sup>2</sup> / 16 – 14AWG [V+] 48VDC, [V-] 0V RJ45 (IZI-Bus)
<b>Miscellaneous:</b>	LED-indications: Housing: Material: Housing colour: IP Class: Weight:	IZI-Link+ status RGB-LED IZI-Bus status RGB-LED DIN-Rail 4-module Desktop ABS plastic Dark grey (RAL7016) housing IP20 95 gram / 3.35 oz
<b>Dimensions:</b>	Housing:	90 x 71 x 58mm / 3.54" x 2.8" x 2.3"
<b>Certifications:</b>	CE / RoHs	
<b>Order code:</b>	TDEL-4010810-A	IZI-PowerCom+, IZI-Link+ PLC-interface

#### Dimensions:

Length / Width / Height: 90 x 71 x 58mm / 3.5" x 2.8" x 2.3"



The **IZI-PowerCom+** is an **IZI-Link+ PowerLine communication interface** module that **sends and receives lighting control data and statuses over a low-voltage 2-wire power line**, allowing you to control, monitor and configure IZI-Link+ compatible products.

This unique technique eliminates additional control wiring which make the installation more reliable and easy to install. The IZI-Link+ system can easily be scaled into a larger network by adding IZI-PowerCom+ modules.

#### Features:

- 720W IZI-Link+ Powerline interface
- High speed 225kbps 2-way communications
- Per IZI-PowerCom+ interface:
  - Up to 256 light control channels
  - Up to 32 IZI-Link+ modules
  - Up to 720Watt of output power
- High constant refresh rate of 40 frames/sec transmit and simultaneously 30 frames/sec receive
- Up to 12 communications channels
- Supports for 2 universes (2 x 512ch)
- Possible to perform background configurations and monitoring during live operation (no black-out)

**Warranty:** 5 years

#### Certifications:

