

IZI-AccessPro

IZI-Link(+) Gateway & Light control system

Technical specifications:

Control:	Control inputs:	RJ45 – Ethernet port DMX-RDM (optically Isolated) DALI (optically isolated) USB (Service port) Contact closure (optically isolated) DMX-RDM THRU (Optically isolated) DMX-RDM / RS485 / IZI-Link RJ45 - IZI-BUS Interface DALI (Optically isolated)
	Control outputs:	
Communication:	Protocols:	Art-Net sACN OSC DMX512-RDM DALI IZI-Link / IZI-Link+ RS485
Power:	Power supply:	24~48VDC
	Power consumption:	2.4 Watt maximum
	Input current:	100mA maximum
Connections:	Power input:	2-pole - WAGO 2231-102
	DALI Input / output:	2-pole - WAGO 714-102
	DMX - RDM input / Thru / output:	3-pole - WAGO 714-103
	Contact closure:	5-pole - WAGO 714-105
	USB input:	USB-B
	Ethernet:	RJ45
	IZI-BUS interface:	RJ45
Miscellaneous:	Housing:	DIN-rail (6 module width)
	Weight:	250 grams / 8.8 oz
	IP-Rating:	IP20
Dimensions:	DIN-Rail housing:	106 x 90 x 58mm 4.18" x 3.6" x 2.3"
LED-indications:	OLED display	128 x 64 pixels white display
	Access status:	RGB-LED
	IZI-BUS status:	RGB-LED
	DALI	Blue LED
	DMX - RDM IN	Blue LED
	DMX - RDM / IZI OUT	Blue LED
	Contact IN	Blue LED
	Art-Net / sACN	Blue LED
Order code:	TDEL-4010785	IZI-AccessPro IZI-Link+ Gateway



The **IZI-AccessPro** is the heart of an **IZI-Link+ system** and this **gateway connects the IZI-Link+ system** with **Art-Net** and **sACN (Ethernet)**, **DMX-512A (RS485)**. **OSC** and **DALI**. The **IZI-AccessPro** outputs **2 universe** with a maximum of **1024 channels**

The IZI-AccessPro is housed in a small DIN-Rail module and has a wide range of connection options, making the module a very useful node.

The special software environment **IZI-supervisor, web interface** and **extensive programmable functions** make this gateway universally applicable.

Features:

- 2 Universe output – 1024 channels
- Art-Net and sACN connectivity
- RDM support
- DMX-512A – RDM In, Thru & Outputs
- IZI-Link(+) IZI-BUS interface
- OLED display with real-time system info
- Realtime Clock with PowerCap & battery
- Programmable scheduler
- Programmable Marco's and rules
- Programmable Soft-Patches
- Programmable Scenes, Sequences, timers and Playbacks
- IZI-touch wall panel support
- Web interface
- Programmable contact inputs
- IZI-Supervisor software suite (Windows)

Warranty: 5 years

